

Single N-channel MOSFET

ELM54874WSA-N

<http://www.elm-tech.com>

■General description

ELM54874WSA-N uses advanced trench technology to provide excellent $R_{ds(on)}$, low gate charge and low gate threshold voltage.

■Features

- $V_{ds}=60V$
- $I_d=12A$
- $R_{ds(on)} = 11m\Omega$ ($V_{gs}=10V$)
- $R_{ds(on)} = 13m\Omega$ ($V_{gs}=6V$)

■Maximum absolute ratings

Ta=25°C. Unless otherwise noted.


Parameter	Symbol	Limit	Unit
Drain-source voltage	V_{ds}	60	V
Gate-source voltage	V_{gs}	± 20	V
Continuous drain current($T_j=150^{\circ}C$)	I_d	12	A
		10	
Pulsed drain current	I_{dm}	40	A
Power dissipation	P_d	2.8	W
		1.8	
Operating junction temperature	T_j	150	°C
Storage temperature range	T_{stg}	- 55 to 150	°C

■Thermal characteristics

Parameter	Symbol	Typ.	Max.	Unit
Thermal resistance junction-to-ambient	$R_{\theta ja}$		62.5	°C/W


■Pin configuration

SOP-8(TOP VIEW)



Pin No.	Pin name
1	SOURCE
2	SOURCE
3	SOURCE
4	GATE
5	DRAIN
6	DRAIN
7	DRAIN
8	DRAIN

■Circuit



Single N-channel MOSFET

ELM54874WSA-N

<http://www.elm-tech.com>

■ Electrical characteristics

Ta=25°C. Unless otherwise noted.







Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
STATIC PARAMETERS						
Drain-source breakdown voltage	BVdss	Id=250µA, Vgs=0V	60			V
Zero gate voltage drain current	Idss	Vds=48V, Vgs=0V		1		µA
		Vds=48V, Vgs=0V, Ta=85°C		30		
Gate-body leakage current	Igss	Vds=0V, Vgs=±20V		±100		nA
Gate threshold voltage	Vgs(th)	Vds=Vgs, Id=250µA	2.0	4.0		V
On state drain current	Id(on)	Vgs=10V, Vds≥10V	40			A
Static drain-source on-resistance	Rds(on)	Vgs=10V, Id=12A		9	11	mΩ
		Vgs=6V, Id=10A		10	13	
Forward transconductance	Gfs	Vds=15V, Id=10A		38		S
Diode forward voltage	Vsd	Is=10A, Vgs=0V		0.8	1.3	V
Max. body-diode continuous current	Is				1.5	A
DYNAMIC PARAMETERS						
Input capacitance	Ciss	Vgs=0V, Vds=30V, f=1MHz		2080		pF
Output capacitance	Coss			320		pF
Reverse transfer capacitance	Crss			120		pF
SWITCHING PARAMETERS						
Total gate charge	Qg	Vds=30V, Vgs=10V Id=10A		35	60	nC
Gate-source charge	Qgs			12		nC
Gate-drain charge	Qgd			10		nC
Turn-on delay time	td(on)	Vgs=10V, Vds=30V RL=1.53Ω, Id=10A Rgen=1.0Ω		10	20	ns
Turn-on rise time	tr			10	20	ns
Turn-off delay time	td(off)			15	30	ns
Turn-off fall time	tf			10	20	ns

Single N-channel MOSFET

ELM54874WSA-N

<http://www.elm-tech.com>


■ Typical electrical and thermal characteristics




Single N-channel MOSFET

ELM54874WSA-N


<http://www.elm-tech.com>




On-Resistance vs. Junction Temperature




Source-Drain Diode Forward Voltage



Drain-Source Breakdown vs. Junction Temperature



Threshold Voltage



Normalized Thermal Transient Impedance, Junction-to-Case


Single N-channel MOSFET

ELM54874WSA-N


<http://www.elm-tech.com>

■ Test circuit and waveform

Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching Test Circuit & Waveforms

